

DATA ELIMINATOR

HD-2 IRONCLADTM HD-2 with IRONCLAD Frasure Verification System



IRONCLAD erasure report



Image of degaussed hard drive

Valuable data demands **IRONCLAD** proof of erasure.

Garner's economical HD-2 degausser with IRONCLAD automated erasure verification and image capture system validates data has been completely eliminated. Fully integrated with the Garner HD-2 hard drive degausser, the IRONCLAD scans the serial number, captures an image of the degaussed hard drive, and records the operator ID and erasure status of degaussed hard drives. This essential information is then preserved in an IRONCLAD erasure report. IRONCLAD provides audit-worthy documentation of the data elimination process.



Garner's HD-2 degausser with IRONCLAD shown

HD-2 IRONCLAD Includes:

- · Garner's economical HD-2 compact degausser
- IRONCLAD erasure report generating software
- · Automated image capture system
- · Touch screen control head
- · Bar-code scanner and stand
- Stylus
- IRONCLAD software support for one year
- 50 "Degaussed" labels for erased hard drives

Why **IRONCLAD**

- HD-2 degausser completely erases all data in 60 seconds
- · Captures and records images of degaussed hard drives
- · Scans serial numbers of degaussed hard drives
- Documents operator ID and erasure status of hard drives
- Generates IRONCLAD erasure report with images for audit purposes
- Creates a secure erasure verification process
- · Provides proof data is completely eliminated

GarnerProducts.com

SCREEN SHOTS



List view of erasure status



Proof of erasure image



The IRONCLAD contains the following interfaces:

- 1. Ethernet
- 2. 4 USB (To connect with: HD-2, bar-code scanner, thumbdrive, or optional mouse, and keyboard)
- 3. HDM
- 4. 3.5 mm Image capture device interface
- 5. Power (Connects to standard wall outlet)

HD-2 IF	RONCLAD SPECIFICATIONS
Product number	HD-2 IRONCLAD
Screen size	7 in.
Storage capacity	16GB
Media	Hard drives: Laptop, standard, network up to 1.5 in. in height Tape media: All LTO, all DLT, AIT, 2590 Series, 8mm, and others
Power supply	HD-2 : 100~240VAC ±5%, 50/60 Hz IRONCLAD : 90~240VAC, 47-440 Hz
Power consumption	HD-2: Standby: 24 Watts Charging: 156 Watts (Avg) During Erase: 60 Watts IRONCLAD: 15W
HD-2 Erasure time with IRONCLAD	Erases up to 45 hard drives per hour
HD-2 Erasure time	Erases up to 480 (1.8 in.) hard drives per hour Erases up to 360 (2.5 in.) hard drives per hour Erases up to 60 (3.5 in.) hard drives per hour
Overall dimensions (HxWxD)	HD-2 IRONCLAD: 10.2 x 17.75 x 18.2 (in.) 260 x 451 x 463 (mm) control head: 6.6 x 9.6 x 2.5 (in.) 168 x 244 x 64 (mm)
Weight	HD-2 IRONCLAD: 40 lbs (18.1 kg) control head: 40 lbs (1.8 kg) *non-shipping weight
Warranty	One-year manufacturer's limited warranty

©2016 Garner Products, Inc. All rights reserved. Patent pending.

Garner Products Inc. 10620 Industrial Avenue Suite 100 Roseville, CA 95678 USA 1-800-624-1903 GarnerProducts.com

Tel: 916-784-0200 Fax: 916-784-1425

